

## Commercial Offer of PTC "Khimvolokno" JSC "Grodno Azot"

PTC “Khimvolokno” JSC “Grodno Azot” is a producer of polyamide yarns and fibers including polyamide industrial yarns for production of cord fabrics, mechanical rubber goods and fishing tackle, cord fabrics (Polyamide, Nylon 6.6, Polyester), BCF yarn of carpet assortment, polyamide and polyamide-based composite materials. Quality Management System was recognized as corresponding to the requirements of International Standard ISO 9001:2008.

In Table 1 there are given Customs Tariff Codes for products of PTC “Khimvolokno”.

**Table 1**

Customs Tariff Code	Product description	Range of use
5402109000	Polyamide industrial yarn	It is designed for production of cord fabrics, technical fabrics for conveyor belts; mechanical rubber goods, packing clothes; fishing tackle, including nets, ropes, cords, etc.; consumer goods, including household goods, leisure and sports goods.
5402410000	Polyamide yarn high-tenacity twisted	
5402200000	Polyester yarn	It is designed for production of cord fabric, technical fabrics, fishing tackle.
5402320000	Polyamide texturized BCF yarn	It is used for production of tufted floor coverings, upholstery materials and other goods
5902101000 59022010000	Cord dipped fabric (Polyamide, Nylon 6.6) Cord dipped fabric (Polyester)	It is used as a multilayer carcass in air tyres.
3908100000	Polyamide -6 granulated	PA-6 is used for manufacturing of injection molding goods, for manufacturing of a wide range of products: polyamide industrial yarn, composite materials with different properties (impact resistant, frost-resistant, waterproof, hardly flammable) and also for manufacturing of different polymer concentrates of dyestuff and thermostabilizers.
3908900000	Grodnamid	It is used in automobile, aircraft and petroleum industry, in machine building and instrument making industry as well as for manufacturing of electronic devices and service tools, household and office appliances.

The lines, such as “Zimmer” – Germany, “Barmag” - Germany, “TMT Machinery Inc.” - Japan, “SwissTex” – Switzerland for manufacturing of polyamide and polyester yarn are in successful operation. The yarn of linear density as follows: dtex 935/940, 1400/1440, 1870/1880 and 2100/2200 is produced nowadays. The products have the world level of quality and are supplied to many countries of Europe, Asia. We offer these products at price 2,05-2,10 EUR/kg, FCA- Grodno, 100% prepayment for the goods lot prepared for shipment.

Availability of advanced, high-technology equipment for weaving and twisting enables us to produce high-tenacity seamless cord fabric of different grades. Cord fabric homologation process was completed successfully at large tire production enterprises. Cord fabric processing and dipping line made by Benninger, Germany, was commissioned and is running successfully. At present our enterprise has mastered the production of more than 30 grades of cord fabrics (Polyamide, Nylon 6.6 and Polyester). Cord fabrics made by PTC “Khimvolokno” are supplied to the markets of Russian Federation, Europe, Asia. We shall be able to offer product prices after consideration of Specifications.

Advanced equipment of famous European companies (Neumag, Volkmann, Power Heat Set) enables us to produce high-quality polyamide BCF yarn and polyamide BCF Heat Set yarn (including Frieze effect).

We are ready to offer polyamide texturized BCF yarn dtex 1000-1800 greige, spun-dyed, bright, dull as well as twisted Heat Set yarn (Suissen technology) in one and two plies (including Frieze effect). In relation to dyeability (affinity) our yarn does correspond to R type (regular, normal) and to class 3.

We offer polyamide BCF yarn at price 2,10-2,20 EUR/kg, twisted Heat Set yarn at price 2,60-2,70 EUR/kg, FCA- Grodno, 100% prepayment for the goods lot prepared for shipment.

Yarn deliveries are effected to the markets of Russian Federation, Europe and China.

Our enterprise renders logistics services for delivery of goods. Shipment may be performed based on any delivery terms as agreed upon with a Buyer. Customs clearance of products is performed at the expense of our enterprise. Order lead time is maximum 30 days after order confirmation.

In addition please find enclosed presentations of the products to be manufactured in English: polyamide industrial yarn (Appendix 1), cord fabric (Appendix 2), polyamide texturized BCF yarn (Appendix 3).

If required to submit paper based catalogues or presentations on electronic media we kindly ask you to let us know the quantity of copies and the postal address for dispatch.

Best regards,

V. I. Rudzinskas,

Vice General Director of JSC “Grodno Azot” –  
Director of PTC “Khimvolokno”

**PTC “Khimvolokno” JSC “Grodno Azot”**

**Legal address of enterprise:** Pr. Kosmonavtov 100, 230013 Grodno, Republic of Belarus

**Postal address of enterprise:** ul. Slavinskogo 4, 230026 Grodno, Republic of Belarus

**Phone / fax:** (+375 152) 54-33-80, 54-34-39

**E-mail:** [office@grodno-khim.by](mailto:office@grodno-khim.by); [market@grodno-khim.by](mailto:market@grodno-khim.by);

[ppm@grodno-khim.by](mailto:ppm@grodno-khim.by); [tnp@grodno-khim.by](mailto:tnp@grodno-khim.by)

**Site:** [www.grodno-khim.by](http://www.grodno-khim.by)

**Vitaly I. Rudzinskas**

Phone: (+375 152) 54-85-50;  
Secretary 54-85-10

**Svetlana I.Kovalchuk (Mrs.)**

Phone: (+375 152) 541804, 738747

**Dzmitry V. Vychov**

Phone: (+375 152) 543308

Vice General Director of JSC “Grodno Azot” –  
Director of PTC “Khimvolokno”

Head of Commercial Department

Chief of Marketing and Sales Department



PTC “KHIMVOLOKNO” JSC “GRODNO AZOT”

The history of **PTC «Khimvolokno» JSC «Grodno Azot»** dates back to December 11, 1971 and that was its construction commencement date.

First industrial yarn for cord fabric and mechanical rubber goods was produced on January 10, 1978. From that moment Grodno company of synthetic yarns has started its production activities.

In 1983 the enterprise was rearranged into Grodno Production Enterprise "Khimvolokno" and reorganization of the state enterprise into Joint Stock Company "Grodno Khimvolokno" was performed in 2002.

Since October 1, 2011 as per decision of extraordinary general meeting of shareholders of both JSC "Grodno Azot" and JSC "Grodno Khimvolokno" the latter was affiliated to JSC "Grodno Azot".

At present PTC «Khimvolokno» is a large manufacturer of polyamide and polyester yarns and fibres, as well as virgin polyamide-6 (PA-6) and PA-6 based composite materials, including:

- PA-6 /granulated/;
- polyamide light&heat-stabilized yarn including spun-dyed one;
- polyamide twisted yarn;
- polyester HMLS yarn;
- polyester twisted yarn;
- polyamide texturized BCF yarn, as well as twisted BCF Heat-set;
- cord fabric for tyre industry both greige and dipped made from polyamide 6, polyamide 6.6 and polyester yarns;
- industrial fabric;
- polymer composite materials;
- consumer goods.

Each of main kinds of goods is manufactured in wide assortment with different physical & mechanical properties and quality indices depending on application range.

## POLYAMIDE 6 BCF TEXTURIZED YARN

**Polyamide 6 BCF texturized yarns** for carpet floor coverings are produced at spin-draw-texturizing-winding equipment of Neumag, Germany. This high-tech equipment enables to manufacture yarn of profile section, bright or dull, undyed or spun-dyed.



We produce:

- polyamide 6 BCF texturized yarn, linear density dtex 1000 – 1800;
- polyamide 6 BCF twisted Heat Set yarn, structure dtex (1000-1800) x 2;
- polyamide 6 BCF twisted Heat Set Frieze yarn, structure dtex (1000-1800) x 2.

Polyamide 6 BCF twisted texturized Heat Set, BCF Frieze are used to produce premium carpet floor coverings of enhanced comfort.

**Polyamide 6 BCF texturized yarn** has a number of advantages when compared with the same kind of polypropylene yarn. Carpet floor covering made of polyamide 6 yarn is highly wear-resistant, antistatic, easy to clean and brings comfort in a room.

High evenness of physic & mechanical parameters and strength of yarn intermingled points coupled with low shrinkage at boiling (within 6-8%) of the yarn, produced by our company, allow to construct carpet floorings in keeping with the best European traditions and up to European standards.



## POLYAMIDE 6 BCF TEXTURIZED YARN

Nominal linear density, dtex	1000, 1100, 1200, 1300, 1800
Deviation of conditional linear density from nominal one, %	±5
Number of filaments	68/128
Tenacity, mN/dtex, min	20.0
Elongation at break, %	28-40
Stretchability, %	9-13
Intermingling points per 1 m, units	25 – 40
Boiling water shrinkage during 10 min., % max	8
Crimpiness (in hot air), %, min	15
Bobbin type	cylindrical
Bobbin weight, kg	(4-4,5)±0,1
Tube dimensions, mm, L/ Ø	292,0 / 73,0
Beam diameter , mm, max	260,0
Remarks	bright , dull, semi-dull, of profile section (trilobal) , undyed, spun-dyed

### PACKING

Each bobbin is wrapped up with PE foil. Bobbins are placed onto pallets with forming a block-pack. Block-packs are stretch-foiled. Standard block-packs are formed on pallets: 1200x1000 mm.



### TRANSPORTATION

Block-packs are carried in 40' containers and trucks

## POLYAMIDE 6 BCF TEXTURIZED HEAT SET YARN

Yarn structure, dtex	1000 x 2 1100 x 2 1200 x 2 1300 x 2 1800 x 2
Deviation of conditional linear density from nominal one, %	±5
Tenacity, mN/dtex, min	20.0
Elongation at break, %	40-70
Number of turns per 1 m of yarn, units	(150-225) ±15
Twist direction	Z (S)
Boiling water shrinkage (15 min), %, max	4,0
Bobbin type	cylindrical
Bobbin weight, kg	(4-4,5)±0,2
Tube dimensions, mm, L/ Ø	292,0 / 73,0
Beam diameter , mm, max	310,0
Remarks	bright , dull, semi-dull, of profile section (trilobal) , undyed, spun-dyed, Frieze

### PACKING

Each bobbin is wrapped up with PE foil. Bobbins are placed onto pallets with forming a block-pack. Block-packs are stretch-foiled. Standard block-packs are formed on pallets: 1200x1000 mm.



### TRANSPORTATION

Block-packs are carried in 40' containers and trucks

The history of **PTC «Khimvolokno» JSC «Grodno Azot»** dates back to December 11, 1971 and that was its construction commencement date.

First industrial yarn for cord fabric and mechanical rubber goods was produced on January 10, 1978. From that moment Grodno company of synthetic yarns has started its production activities.

In 1983 the enterprise was rearranged into Grodno Production Enterprise "Khimvolokno" and reorganization of the state enterprise into Joint Stock Company "Grodno Khimvolokno" was performed in 2002.

Since October 1, 2011 as per decision of extraordinary general meeting of shareholders of both JSC "Grodno Azot" and JSC "Grodno Khimvolokno" the latter was affiliated to JSC "Grodno Azot".

At present PTC «Khimvolokno» is a large manufacturer of polyamide and polyester yarns and fibres, as well as virgin polyamide-6 (PA-6) and PA-6 based composite materials, including:

- PA-6 /granulated/;
- polyamide light&heat-stabilized yarn including spun-dyed one;
- polyamide twisted yarn;
- polyester HMLS yarn;
- polyester twisted yarn;
- polyamide texturized BCF yarn, as well as twisted BCF Heat-set;
- cord fabric for tyre industry both greige and dipped made from polyamide 6, polyamide 6.6 and polyester yarns;
- industrial fabric;
- polymer composite materials;
- consumer goods.

Each of main kinds of goods is manufactured in wide assortment with different physical & mechanical properties and quality indices depending on application range.

## Dipped heat-set cord fabrics

Dipped heatset cord fabrics (hereinafter referred to as cord fabrics) that possess high rubber adhesion are used as reinforcing material in production of pneumatic tyres.

The enterprise produces wide range of cord fabrics made of polyamide-6, polyamide-6.6, polyester.

**Nylon (PA-6) cord fabric** is characterized by high tenacity, moisture resistance, resistance to heat ageing, high durability at multiple tensile strains, stretching-compression and impact stress and to be used as carcass in pneumatic tyres for cars and trucks, agricultural machines.



There are mastered production and sales of 12 standard grades of nylon cord fabrics that are of demand at tyre manufacturers as high quality goods. Among fabric grades being produced there is a special demand in fabric grades with lower surface density such as: 30 (302) KNTS-P from the yarn of structure tex 187x1x2 and 22 (222) KNTS-P from yarn of structure tex 144x1x2.

Usage of cord fabric with lower surface density in construction of pneumatic tyres allows to reduce consumption per a tyre of not only cord fabric but rubber too, having reduced tyre weight while keeping its strength, whereby increasing tyre durability and reducing car fuel consumption.

**Anid (PA6.6) cord fabric** unlike to nylon cord fabric possesses higher resistance to heat ageing, higher durability and lower elongation that allows to reduce tyre wearing and increase tyre run life. Thanks to specific features, anid cord fabric is used for manufacture of tyres used in difficult road conditions and at high loads particularly for

production of heavy and super heavy tyres, aircraft tyres. The company produces and sells 14 grades of cord fabric for reinforcement of tyres:

30 (302) ADU-P from the yarn of structure dtex 2100x1x2;

35(352) ADU-P (dtex 2100x1x2); 42(422) ADU-P (dtex 1880x1x3); 133 ADU-P, 133 A-P (dtex 940x1x2); 13ATLDU-P, 132 A-P (dtex 940x1x2); 25ATLDU-P (dtex 1880x1x2); 252 A-P (dtex 1880x1x2), 21(212) A-P (dtex 1400x1x2) and 10 grades of cord fabric for reinforcement of aircraft tyres: 13 A-P (A), 132 A-P (A), 133 A-P (A), 28 (282) A-P (A), 30 (302) A-P (A), 30 (302) ADU-P (A), 55 A-P (A).

**Polyester cord fabric** is used as carcass in pneumatic tyres for passenger cars and lightweight trucks. Polyester cord fabric in comparison with nylon (PA-6) and anid (PA-6.6) fabrics possesses higher moisture resistance and, as a consequence, is of less effect in tensile characteristics of fabric due to moisture influence. Tyres produced with polyester cord fabrics possess good wear resistance, low noise.

The enterprise produces polyester cord fabrics 18PDU-P (tex 148x1x2), 21 PDU-P (tex 167x1x2), 27 PDU-P (tex 220x1x2) from HMLS (high modulus low shrinkage) polyester yarns.



All assortment of cord fabrics and for nylon fabrics starting from initial stage (polyamidation of caprolactam) till final stage (dipping and heatsetting) is produced at the company, on high-technology equipment of leading global producers of equipment.

Cord fabrics produced meet world level by qualitative characteristics and are of demand on cord fabric markets.

Main advantages of cord fabrics are as follows:

- high strength
- absence of knots (seams)
- high evenness of warp yarn distribution along fabric width
- high evenness of physical and mechanical data of warp yarns

Besides standard grades PTC "Khimvolokno" JSC "Grodno Azot" produces dipped cord fabrics under customers' specifications

## NYLON DIPPED CORD FABRIC

It is used in tyre industry as reinforcing material for manufacturing pneumatic tyres

Fabric grade, KNTS-P	123 KNTS-P	21/212 KNTS-P	22/222 KNTS- P Instead of 23/232	22/222 KNTS-P Instead of 25/252	30/302 KNTS-P	35/352 KNTS-T-P
Cord fabric structure, dtex	935x1x2	1440x1x2	1440x1x2	1440x1x2	1870x1x2	1550x1x3
Breaking strength, N, min	120/118	201 / 196	211 / 206	211 / 206	290 / 285	328 / 325
Thickness, mm	0,55±0,03	0,66±0,03	0,62±0,03	0,62±0,03	0,75±0,03	0,78±0,03
Stiffness, cN	max 200	max 350/300	245±50	245±50	max 350/300	245±50
Twist direction	ZZS					
Hot air shrinkage at 160° C, 20 min, %, max	7,5					
Elongation %:						
-at break	20,0±2,0	23,0±2,0	22,0±2,0	22,0±2,0	23,0±2,0	22,0±2,0
- at 20N	5,0 ±1,0	3,0±1,0	3,0±1,0	3,0±1,0	3,0±1,0	2,5±1,0
-at 39 N	7,5±1,0	6,0±1,0	6,0±1,0	6,0±1,0	6,0±1,0	5,5±1,5
Adhesion, N, min	100	130	130	130	137	170
Twist per 1 m:						
-single twist	460 ±20	370±20	350±20	350±20	326±20	225±20
-cord twist	460 ±20	360±20	330±20	330±20	318±20	220±20
Total number of ends per 10 cm :						
- by warp	64 ± 1	111±1/89±1	106±1/84±1	112±1/89±1	99±1/79±1	91±1/79±1
- by weft	9 ± 1	7±1/9±1	7±1	7±1	7±1/9±1	7±1
Dip pick up, %	4,5±1,0					
Fabric width, cm	140±2					

### PACKING

Dipped cord fabric preliminarily wound on a shell is packed in the way as follows:

- a roll is wrapped up with foamed polyethylene of 3 mm thickness. Each roll end is put on with two cardboard circles with bags consisting moisture absorbing substance preliminarily fixed on it. A roll together with a shell is wrapped up with black polyethylene stretch-foil of 23 µm thickness and 15-25 revolutions of packing machine, and is put on with a case of polypropylene industrial fabric.

### TRANSPORTATION

Cord fabric is carried in 40' containers, boxcars and trucks

## POLYESTER DIPPED CORD FABRIC

It is used in tire industry as reinforcing material for manufacturing pneumatic tires

Style	18 PDU-P	21 PDU-P	27 PDU-P
Cord fabric structure, dtex	1480x1x2	1670x1x2	2200x1x2
Tensile strength, N , min	178,0	200,0	265,0
Thickness, mm	0,63±0,03	0,69±0,03	0,80±0,03
Stiffness, cN	90-190		
Twist direction	ZZS		
Hot air shrinkage at 160° C, 20 min, %, max	2,0±0,5		
Elongation %	(20H)	(39H)	(45H)
- at load	1,8±0,5	2,8±0,5	2,2±0,5
- at load	(39H)	(90H)	(90H)
- at break	3,5±0,6 17,0±2,0	5,9±1,0 17,0±2,0	5,7±1,0 17,0±2,0
Adhesion, N, min	137	150	157
Twist per 1 m			
Single twist	380±20	350±15	325±15
Cord twist	370±20	350±15	325±15
Total number of ends per 10 cm, pcs			
- by warp	115±1	80±1	92±1
- by weft	8±1	8±1	8±1
Dip pick up ,%	3,0±1,0	2,4±1,0	3,0±1,0
Fabric width, cm	140±2,0		
Number of ends per fabric width	1613	1120	1288
Nominal linear density of cotton-PA 66 weft yarn , tex	22		
Actual moisture, %, max	0,8		

### PACKING

Dipped cord fabric preliminarily wound on a shell is packed in the way as follows:

- a roll is wrapped up with foamed polyethylene of 3 mm thickness. Each roll end is put on with two cardboard circles with bags consisting moisture absorbing substance preliminarily fixed on it. A roll together with a shell is wrapped up with black polyethylene stretch-foil of 23 μm thickness and 15-25 revolutions of packing machine, and is put on with a case of polypropylene industrial fabric.

### TRANSPORTATION

Cord fabric is carried in 40' containers, boxcars and trucks

## ANIDE (PA-66) DIPPED CORD FABRIC

It is used in tire industry as reinforcing material for manufacturing pneumatic tires

Fabric grade	30 ADU-P	302 ADU-P	35 ADU-P	352 ADU-P	13 ATLDU-P	132 ADU-P	25 ATLDU-P	133 ADU-P
Cord fabric structure	2100x1x2	2100x1x2	2100x1x2	2100x1x2	940x1x2	940x1x2	1880x1x2	940x1x2
Breaking strength, N, min	304	304	340	340	135	135	260	135
Thickness, mm	0,80±0,05	0,80±0,05	0,78±0,03	0,78±0,03	0,56±0,04	0,56±0,04	0,74±0,04	0,56±0,04
Stiffness, cN	max 250	max 250	max 250	max 250	140±60	140±60	175±75	max 200
Twist direction	ZZS							
Hot air shrinkage ( $t^{\circ} = 160^{\circ}\text{C}$ , $t = 20$ min) % - $4,0 \pm 0,8$ * If agreed with a customer other test methods and correspondingly other nominal values are admitted								
Elongation %: - at 20 N	2,0±0,5	2,0±0,5	2,0±0,5	2,0±0,5	4,9±1,0	4,9±1,0	2,5±1,0	-
- at 39 N	4,0±1,0	4,0±1,0	4,0±0,9	4,0±0,9	8,0±1,0	8,0±1,0	5,5±1,0	-
- at 44 N	-	-	-	-	-	-	-	8,7±0,9
- at 100 N	9,0±0,9	9,0±0,9	9,0±0,9	9,0±0,9	-	-	-	-
- at break	22,0±2,0	22,0±2,0	22,0±2,0	22,0±2,0	20,0±2,0	20,0±2,0	22,0±2,0	19,0 min
Adhesion, N, min	170	170	170	170	100	100	147	100
Twist per 1 m: -single twist	305±20	305±20	305±20	305±20	470±20	470±20	330±20	470±20
-cord twist	305±20	305±20	305±20	305±20	470±20	470±20	330±20	470±20
Total number of ends per 10 cm : - by warp	96±1	76±1	96±1	76±1	132±1	94±1	94±1	63±1
-by weft	8±1	8±1	8±1	8±1	11±1	9±1	11±1	8±1
Dip pick up, %	5,0±1,0	5,0±1,0	5,0±1,0	5,0±1,0	5,0±1,0	5,0±1,0	5,0±1,0	5,0±1,0
Fabric width, cm	140±2	140±2	140±2	140±2	140±2	140±2	140±2	140±2
Total cords, pcs	1340	1070	1340	1070	1848	1316	1316	880
Nominal linear density: cotton-anide weft, tex	22	22	22	22	22	-	22	22
cotton weft, tex					-	25, 30	-	-
Actual moisture, %, max	1,0							

### PACKING

Dipped cord fabric preliminarily wound on a shell is packed in the way as follows:

- a roll is wrapped up with foamed polyethylene of 3 mm thickness. Each roll end is put on with two cardboard circles with bags consisting moisture absorbing substance preliminarily fixed on it. A roll together with a shell is wrapped up with black polyethylene stretch-foil of 23 mm thickness and 15-25 revolutions of packing machine, and is put on with a case of polypropylene industrial fabric.

### TRANSPORTATION

Cord fabric is carried in 40' containers, boxcars and trucks

**PTC “KHIMVOLOKNO” JSC “GRODNO AZOT”**

**WWW.GRODNO-KHIM.BY**

**E-MAIL: MARKET@GRODNO-KHIM.BY**

**PHONE +375 152 51 49 04 (MARKETING)**

**THANK YOU FOR YOUR ATTENTION!**

**PTC “KHIMVOLOKNO” JSC “GRODNO AZOT”**